



HMIS Rating
 WHMIS Hazard
 Class: Non-Hazardous

MATERIAL SAFETY DATA SHEET

GENERAL INFORMATION

PRODUCT NAME OR NUMBER (as it appears on label) VELOCITY™ Cable Pulling Lubricant		CATALOG NUMBER All "31" Series
MANUFACTURER'S NAME IDEAL INDUSTRIES, INC.		EMERGENCY TELEPHONE NO. (815) 895-5181
ADDRESS (Number, Street, City, State, Zip Code) Becker Place, Sycamore, IL 60178		
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD CLASS, HAZARD ID NO. (49 CFR 172.101) None		
CHEMICAL DESCRIPTION Polymer-based Mixture	FORMULA Proprietary	

SECTION I - INGREDIENTS

CAS REGISTRY NO.	%W	CHEMICAL NAME(S)*	Listed as a carcinogen in NTP, IARC or OSHA 1910(z) (specify)
7732-18-5	<98	Water	No
26062-79-3	<1	diallyldimethylammonium chloride 20% aqueous solution	No
26590-05-6	<5	Poly(2-propene-1-aminiun,N-dimethyl-N-2-propenyl chloride-co-acrylamide)	No
57-55-6	<0.5	Propylene Glycol	No
8042-47-5 24838-91-8	<1	Acrylamide Sodium Acrylate Copolymer with Trideceth-6	No
52-51-7	<0.1	2-Bromo-2-Nitropropane 1,3 Diol	No

SECTION II - PHYSICAL DATA

BOILING POINT 212°F 100°C	SPECIFIC GRAVITY (H ₂ O=1) 0.98	PERCENT VOLATILE BY VOLUME (%) <90
SOLUBILITY IN WATER Moderate	pH = 6.50 - 8.0	PERCENT SOLID BY WEIGHT (%) <5
APPEARANCE AND ODOR Ivory translucent gel	IS MATERIAL: LIQUID SOLID <u>GEL</u> GAS PASTE POWDER	

SECTION III - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT None	method used C.C.C.	FLAMMABLE LIMITS	LEL None	UEL None
EXTINGUISHING MEDIA Use extinguishing media suitable for surrounding materials.				
SPECIAL FIRE FIGHTING PROCEDURES Self-contained respiratory protection should be provided for fire fighters. Keep fire exposed containers cool with water.				
UNUSUAL FIRE AND EXPLOSION HAZARDS None				

* None of the chemical raw materials contained in this formulation are considered hazardous under the Federal Hazards Communication Standard 29 C. F. R 1910.1200

SECTION IV - HEALTH HAZARD INFORMATION

EFFECTS OF OVEREXPOSURE - Conditions to Avoid	None normally expected. Upon prolonged contact may cause temporary eye discomfort.
THRESHOLD LIMIT VALUE	NF
PRIMARY ROUTES OF ENTRY	Inhalation <input type="checkbox"/> Skin Contact <input checked="" type="checkbox"/> Other (specify)
EMERGENCY FIRST AID PROCEDURES	
SKIN CONTACT:	Wash with soap and water for 15 minutes
EYE CONTACT:	Flush with water for 15 minutes. Inhalation - Move to fresh air
INGESTION:	Induce vomiting. Consult physician or local poison control center

SECTION V - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID	None
	STABLE	X		
INCOMPATIBILITY (materials to avoid)				
Avoid strong oxidizers				
HAZARDOUS DECOMPOSITION PRODUCTS:				
Excessive heat and burning may release oxides of carbon and nitrogen				
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID	None
	WILL NOT OCCUR	X		

SECTION VI - SPILL AND LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED	
Wipe up, shovel or vacuum spilled material. Clean up spills immediately as they can be dangerously slippery.	
WASTE DISPOSAL METHOD	
Comply with Federal, state and local regulations for solid landfill	
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs)	
None Required	
RCRA HAZARDOUS WASTE NO. (40CFR 261.33)	
None Required	
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water)	
None	
^a Theoretical _____ lb/gal	N/A
^b Analytical _____ lb/gal	N/A

SECTION VII - PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (specify type)				
None normally required				
VENTILATION	LOCAL EXHAUST (Specify Rate)	None	SPECIAL	None
	MECHANICAL (General) (Specify Rate)	Recommended in closed areas	OTHER	None
PROTECTIVE GLOVES (specify type)		EYE PROTECTION (specify type)		
None normally needed - Neoprene if necessary		Safety glasses or splash goggles		
OTHER PROTECTIVE EQUIPMENT				
Eye fountain in work area is recommended				

SECTION VIII - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	
Store at temperatures between 40 - 120° F. Avoid freezing	
OTHER PRECAUTIONS	
Keep away from children, infants and pets	

SECTION IX - ADDITIONAL INFORMATION

If material is used in extreme heat (>120° F), prolonged and repeated exposure could pose a risk of pulmonary disease. Exposure below mist TLV (5mg/m) appears to be without risk.	
N/A = Not Applicable, N.E. = None Established	

THIS MATERIAL SAFETY DATA SHEET PREPARED BY:

NAME	James R. MacMurdo	SIGNATURE <i>James R. MacMurdo</i>
TITLE	Director, Corporate Quality Assurance	
TE	03/10/2006	